

Innovative | Interactive | Intelligent

The 2700 CE is the most advanced, next generation ATM for the retail market.

Design

The modern, yet simple design of the 2700 CE looks like no other ATM before its time. The elegant lines of the 2700 CE allows it to fit in, and even enhance, any setting. The optional LED topper or LCD topper are powerful advertising tools and seamless extensions of the ATM.

Dynamic User Interface



The 2700 CE's highly advanced user interface and graphics compliments the design. Enhanced features include streaming news and weather updates, background changes, advertising capability, and vibrating touch screen.

More Power and Security

The ARM v7 Cortex A8 834MHz CPU, has expert data processing capabilities to power multitasking, networking, and enhanced graphics & audio.

Enhanced security features ensure the highest level of security of any ATM:

Security Options

- Anti-Skimming (Skimmer's device detector)
- Security Pack (Thermal Sensor, Vibration Sensor, Local Siren)
- Auto remote report (with RMS system)
- Enhanced safe door and locking mechanism



Innovative | Interactive | Intelligent

The 2700 CE is the most advanced, cost effective ATM on the market.



System Control

- ARM v7 Cortex A8
- Microsoft® Windows CE 6.0

Customer Display

- 10.2" TFT LCD

Communication

- TCP/IP (SSL configurable)

Optional

- Dial-up

Input Type

- 4x2 touch function keys

Optional

- 10.2" TFT touch screen with vibrating feedback

Languages

- English
- Spanish
- French

Card Handling

- Dip-type card reader

Optional

- IC card reader EMV Level 1, 2 compliant

Cash Dispensing

- 1,000 or 2,000-note removable cassette
Up to Three cassettes

Printers

- 80 mm graphical thermal receipt printer

Security

- UL Business Hour safe
- Mechanical combination lock
- Security Options
 - UL Level 1 safe
 - Electronic safe lock
 - KABA Mas Cencon safe lock
 - Alarm Box Option
 - Proximity Sensor Option
 - Camera Option

Power Supply

- AC 110–230V, 50–60 Hz

Operating Environment

- Temperature: -32°F–104°F
- Humidity: 25%–85%

Dimension and Weight

- Height: 52.3" (1,328 mm)
- With Topper: 66.3" (1,685 mm)
- Width: 15.7" (400 mm)
- Depth: 18.4" (468 mm)
- Weight: 265 lbs (120 kg)



Illuminated Topper

Optional Double sided LED Back-Light
Optional 15" LCD

LED Back-Lit ATM Sign

Function Keys

(4x4 touch function keys)

Receipt Printer

Graphical thermal printer
Prevents paper jam
80 mm thermal receipt paper
Automatic paper loading and cutting

Customer Display

10.2" wide TFT Color LCD
Infrared Touch Screen Option

Card Reader

Dip hybrid card reader
EMV level 1, 2 support (EMV 4.0)

EPP

PCI compliant EPP
Triple DES compliant
RKT Option

Cash Dispensing Unit

Up to 3 cassettes containing 1,000 or 2,000 bank notes
Dispensing speed 6 notes per second
Double detection sensor
Reject cassette